


Middle East

Product Guide



Innovation & Expertise

Marley systems

Marley Plumbing & Drainage offer a complete range of above and below ground drainage systems, manufactured to exacting UK and European standards and designed for commercial and large-scale developments as well as smaller projects. Products are produced within the BS EN ISO 9001 system of supervision and control of Quality management systems and bear the BSI Kitemark where appropriate. All products are packed appropriately for shipment to a worldwide network of distributors.

Product specification information

This guide contains detailed product specification information together with design and installation information for the Marley PVCu soil & waste, Multikwik WC connectors, aluminium roof outlets and underground drainage ranges.

Production information

Information on the complete range of Marley Plumbing and Drainage system solutions is available to download from aliaxis-gulf.com




Contents

4 The Marley Range	34 WC Manifold systems
6 Solvent waste, PVCu	36 PVCu floor outlets & Ancillaries
8 Solvent waste, ABS	37 PVCu flat roof outlets
10 Push-fit soil, PVCu	38 Traps
16 Solvent soil, PVCu	46 Solid wall drainage systems & Inspection Chambers
23 Active drainage	57 Installation guidance
24 Accessories	66 Standards
26 WC Connectors	

Solid wall system

- 82mm, 110mm & 160mm diameters
- Private drainage
- Plain ended and socketed pipe
- Adaptors to other materials
- Access fittings
- 250mm and 450mm inspection chambers
- Adjustable and variable bends
- A wide range of gullies
- Manufactured to BS EN 1401
- BBA 88/1977 certification
- A number of solid wall fittings are also suitable for use with 150mm quantum and highway pipes.



Traps

Designed by our plumbing experts, the Multikwik traps range is a comprehensive suite of products which provide reliable solutions for both typical and more challenging installations.

From standard traps for basins, baths and showers to more complex utility traps and nozzles for appliance connections, the Multikwik range has a product suited to the job.

WC Connectors

Thanks to the flexible EVA and reliable TPE seals, the Multikwik WC connectors allow for imperfect pipes and spigots, while still ensuring a watertight joint past the point of installation – ideal for tolerating movement and WC load bearing pressures. The seals and multidepth fins give additional peace of mind for a secure seal.



PVCu soil and waste systems

The PVCu soil system is available in 82, 110 and 160mm diameters, with push-fit and solvent weld options incorporating socketed and plain ended pipe.

110 and 160mm pipe support components have been designed specifically to support horizontal or vertical suspended PVCu pipework.

Pipes and fittings are also suitable for use as internal and external rainwater pipes to drain flat roofs and metal gutter systems on commercial and industrial buildings.



High rise buildings

Marley Plumbing & Drainage are specialists in sanitary pipework products, with a PVC soil & waste range available in diameters up to 200mm which is suitable for most high-rise building applications.

PVC soil stack installations can also incorporate sound reduction or HDPE sections, if necessary. Please contact your local sales representative to discuss your requirements.

Marley Technical Services design drainage pipework systems using the three methods of soil stack ventilation; secondary ventilation, single stack system with Stack-Aerator and active drainage ventilation using Studor P.A.P.A. and AAVs. For further product information on the Studor range, please see page 23.

Solvent waste, PVCu


PIPE




Size mm	Code	Length	Colour	Qty
32	KP104AE	4m	W B G	10
40	KP204AE	4m	W B G	10
50	KP304AE	4m	W B G	5

Double spigot

STRAIGHT COUPLINGS




Size mm	Code	A	B	Colour	Qty
32	KSC1	46	20	W B G	60
40	KSC2	53	24	W B G	30
50	KSC3	66	28	W B G	30



Size mm	Code	A	B	C	Colour	Qty
32	KEC1	86	61	20	W G	10
40	KEC2	90	64	23	W G	10
50	KEC3	82	50	30	W G	10


Expansion/adaptor

PIPE CLIPS



Size mm	Code	A	B	Colour	Qty
32	KF1	57	30	W B G	100
40	KF2	62	30	W B G	100
50	KF3	77	41	W B G	80


Open PVCu



Size mm	Code	A	B	Colour	Qty
32	WC3	76	30	W B G	100
40	WC4	82	30	W B G	100
50	WC5	100	38	W G	80


Saddle

BENDS




Size mm	Code	Angle	A	B	Colour	Qty
32	KB1	88½°	57	18	W B G	50
40	KB2	88½°	62	21	W B G	30
50	KB3	88½°	78	28	W B G	10

Solvent sockets



Size mm	Code	Angle	A	B	Colour	Qty
32	KB12	45°	29	18	W B G	10
40	KB22	45°	33	21	W B G	20
50	KB32	45°	42	28	W B G	20


Solvent sockets



Size mm	Code	Angle	A	B	Colour	Qty
32	KBA12	45°	24	23	W G	40
40	KBA22	45°	35	26	W G	20


Solvent socket/spigot

BENDS



Size mm	Code	Angle	A	B	C	D	Colour	Qty
40	KBK25	90°	48	48	23	23	W B G	20
50	KBK35	90°	59	50	20	28	W G	10


Knuckle bend/boss adaptor KBK35 is a Radius Bend which can solvent weld over a boss upstand



Size mm	Code	Angle	A	B	Colour	Qty
32	KBS1	87½°	92	18	W G	20
40	KBS2	87½°	92	23	W G	20


Solvent socket/spigot

TEES



Size mm	Code	Angle	A	B	Colour	Qty
32	KT1	88½°	92	57	W B G	30
40	KT2	88½°	106	62	W B G	20
50	KT3	88½°	135	78	W B G	10


Solvent sockets



Size mm	Code	Angle	A	B	Colour	Qty
40	KT21	45°	117	78	W G	20
50	KT31	45°	149	100	W G	10

Solvent sockets


CROSS TEE



Size mm	Code	Angle	A	B	Colour	Qty
40	KXT21	88½°	106	62	W G	10
50	KXT31	88½°	140	87	W G	10


Solvent sockets

ACCESS PLUG



Size mm	Code	A	B	C	Colour	Qty
32	KAP1	22	53	8	W B G	10
40	KAP2	25	57	8	W B G	10
50	KAP3	33	71	8	W B G	10

SOCKET REDUCER



Size mm	Code	A	B	Colour	Qty
32-21.5	KR175	22	20	W G	100
40-32	KR210	28	22	W B G	80
50-32	KR310	32	28	W G	40
50-40	KR320	32	28	W B G	40

Solvent spigot/socket

IRON ADAPTORS



Female

Size mm	Code	A	B	C	Colour	Qty
32	KFA1	50	25	20	W G	10
40	KFA2	53	25	24	W G	10
50	KFA3	60	25	28	W G	10

Solvent socket/BSP thread

Male

Size mm	Code	A	B	C	Colour	Qty
32	KMA1	44	20	20	W G	50
40	KMA2	47	20	24	W G	40
50	KMA3	53	20	28	W G	40

Solvent socket/BSP thread


Solvent waste, ABS

PIPE



Size mm	Code	Length	Colour	Qty
32	WAP34	4m	W B G	♥ 10
40	WAP44	4m	W B G	♥ 10
50	WAP54	4m	W B G	♥ 5

STRAIGHT COUPLINGS




Size mm	Code	A	B	Colour	Qty
32	WAC3	40	20	W B G	♥ 40
40	WAC4	46	23	W B G	♥ 30
50	WAC5	63	30	W B G	♥ 30

Size mm	Code	A	B	C	Colour	Qty
32	WAC31	86	61	20	W	♥ 10
40	WAC41	90	64	23	W	♥ 10
50	KEC3*	82	50	30	W	♥ 10

Expansion/copper adaptor

PIPE CLIPS




Size mm	Code	A	B	Colour	Qty
32	KF1	57	30	W B G	♥ 100
40	KF2	62	30	W B G	♥ 100
50	KF3	77	41	W B G	♥ 80

Open PCVu

Size mm	Code	A	B	Colour	Qty
32	WC3	76	30	W B G	♥ 100
40	WC4	82	30	W B G	♥ 100
50	WC5	100	38	W	♥ 80

Saddle

BENDS



Size mm	Code	Angle	A	B	Colour	Qty
32	WAB3	88½°	55	20	W B G	♥ 50
40	WAB4	88½°	64	23	W B G	♥ 30
50	WAB5	88½°	86	30	W B G	♥ 20

Size mm	Code	Angle	A	B	Colour	Qty
32	WAB31	45°	32	20	W B G	40
40	WAB41	45°	36	23	W B G	♥ 20
50	WAB51	45°	47	30	W B G	♥ 20

Size mm	Code	Angle	A	B	Colour	Qty
32	WAB32	45°	45	20	W	30
40	WAB42	45°	48	23	W	♥ 20

Spigot

Size mm	Code	Angle	A	B	Colour	Qty
32	WAB33	90°	44	20	W B G	♥ 30
40	WAB43	90°	53	23	W B G	♥ 20


Knuckle bend

ACCESS PLUG



Size mm	Code	A	B	C	Colour	Qty
32	WAA3	22	53	8	W B G	♥ 10
40	WAA4	25	57	8	W B G	♥ 10
50	WAA5	33	71	8	W B G	♥ 10


TEES



Size mm	Code	Angle	A	B	Colour	Qty
32	WAT3	88½°	90	55	W B G	♥ 30
40	WAT4	88½°	107	64	W B G	♥ 20
50	WAT5	88½°	140	86	W B G	♥ 10

Size mm	Code	Angle	A	B	Colour	Qty
32	WAT31	45°	102	65	W	♥ 20
40	WAT41	45°	117	79	W	♥ 20
50	WAT51	45°	150	100	W	♥ 10

CROSS TEE




Size mm	Code	Angle	A	B	Colour	Qty
40	WAT42	88½°	106	65	W	♥ 10
50	WAT52	88½°	140	88	W	♥ 10

SOCKET REDUCER



Size mm	Code	A	B	Colour	Qty
40-32	WAR43	26	20	W B G	♥ 80
50-32	WAR53	31	20	W B G	♥ 40
50-40	WAR54	31	23	W B G	♥ 40

IRON ADAPTORS



Female

Size mm	Code	A	B	C	Colour	Qty
32	WAF3	50	25	25	W	♥ 10
40	WAF4	53	25	24	W	♥ 10
50	WAF5	60	25	28	W	♥ 10

Male

Size mm	Code	A	B	C	Colour	Qty
32	WAM3	44	20	20	W	♥ 50
40	WAM4	47	20	24	W	♥ 40
50	WAM5	53	20	28	W	♥ 40


CAP AND LINING



Size mm	Code	A	Colour	Qty
32	WAM31	58	W	♥ 10

Push-fit soil, PVCu

PIPE



Size mm	Code	Length	A	B	Colour	Qty
82	SP303	3m	100	76	B G	♥ 156
82	SP304	4m	100	76	G	♥ 156




110MM CO-EX SOIL

110	SP4025	2.5m	128	70	B G	♥ 100
110	SP403	3m	128	70	W B G	♥ 100
110	SP404	4m	128	70	G	♥ 100

160	SP603	3m	182	107	G	♥ 46
160	SP604	4m	182	107	G	♥ 46

Push-fit socket

STRAIGHT COUPLINGS



Loose pipe socket

Size mm	Code	A	B	C	Colour	Qty
82	SE300	103	50	48	B G	♥ 30
110	SE400	109	61	48	W B G	♥ 8
160	SE600	190	107	77	G	♥ 4



Double ring seal slip coupling

Size mm	Code	A	B	Colour	Qty
82	SE305	104	49	B G	♥ 30
110	SE405	128	64	B G	♥ 8
160	SE605	170	83	G	♥ 4

Triple socket

Size mm	Code	A	B	Colour	Qty
110	SE402	311	82	G	♥ 4

SHORT RADIUS BENDS



Size mm	Code	Angle	A	B	C	Colour	Qty
82	SB31	87½°	138	115	49	B G	♥ 20
110	SB41	87½°	158	157	70	W B G	♥ 4
160	SFB61	87½°	242	232	88	G	♥ 1

Push-fit socket/spigot



Size mm	Code	Angle	A	B	C	Colour	Qty
82	SB35	45°	76	73	49	B G	♥ 20
110	SB45	45°	84	89	62	W B G	♥ 4
160	SFB65	45°	120	118	85	G	♥ 2

Push-fit socket/spigot

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SB411	88½°	135	145	50	B G	♥ 4

Double push-fit socket

ADJUSTABLE BENDS



Size mm	Code	Angle	A	B	C	Colour	Qty
82	SB37	11-87½°	195	187	49	B G	10

Push-fit socket/spigot

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SB46	5-14°	125	135	82	G	4

Push-fit socket/spigot



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SB47	21-90°	189	187	90	127	B G	4

Push-fit socket/spigot

Size mm	Code	Angle	A	B	C	D	Colour	Qty
160	SB67	31-90°	285	275	96	184	G	2

Push-fit socket/spigot

OFFSET BENDS





Size mm	Code	Angle	A	B	C	Colour	Qty
110	SNE405	67½°	94	91	60	W B G	4

Push-fit solvent socket

Size mm	Code	Angle	A	B	C	Colour	Qty
82	SNE300	67½°	98	86	57	B G	30
160	SNE600	67½°	178	182	88	G	140

Push-fit solvent socket.

EQUAL BRANCHES




Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SY401	87½°	299	150	60	175	W B G	4
160	SY601	87½°	438	245	96	260	G	2

Size mm	Code	Angle	A	B	C	Colour	Qty
82	SY36	45°	229	130	55	G	10
110	SY460	45°	285	198	62	B G	4
160	SY63	45°	400	200	90	G	2

Push-fit sockets/spigot

Push-fit soil, PVCu


EQUAL BRANCHES



Size mm	Code	Angle	A	B	C	Colour	Qty
110	SY466	45°	282	198	62	B G	4

Push-fit sockets/solvent socket


FIVE BOSS BRANCHES



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SY405	87½°	287	143	60	175	W B G	4


Push-fit sockets/spigot

THREE BOSS BRANCH



Size mm	Code	Angle	A	B	C	D	Colour	Qty
82	SY33F	87½°	212	122	52	121	B G	10


UNEQUAL BRANCHES



Size mm	Code	Angle	A	B	C	Colour	Qty
160x110	SY64	87½°	337	175	175	G	2

Push-fit sockets/spigot. 2 boss/access upstands


UNEQUAL BRANCHES



Size mm	Code	Angle	A	B	Colour	Qty
160x110	SY66	45°	335	306	G	2

Push-fit sockets/spigot


DOUBLE BRANCH



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SY404	87½°	288	141	54	76	G	4

Push-fit sockets/spigot. 2 boss/access upstands


CORNER BRANCH



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SY411°	87½°	287	143	60	175	G	4

Push-fit sockets/spigot. 1 boss upstand


BOSS PIPES



Size mm	Code	Angle	A	B	C	Colour	Qty
110	SW41	87½°	204	86	82	W B G	4

Push-fit socket/spigot. 1 40mm boss connection

BOSS PIPES



Size mm	Code	Angle	A	B	C	Colour	Qty
82	SW30	90°	202	101	49	B G	15


Push-fit socket/spigot. 3 boss upstands, 1 drilled

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SW40	90°	244	123	70	W B G	4

Push-fit socket/spigot. 4 boss upstands

Push-fit soil, PVCu

ACCESS PIPES




Size mm	Code	A	B	C	Colour	Qty
82	SF31	205	101	52	B G	15

Size mm	Code	A	B	C	D	Colour	Qty
110	SF41	244	123	70	152	B G	4

Socket/spigot

REAR ACCESS BENDS




Size mm	Code	Angle	A	B	C	Colour	Qty
110	SB42	87½°	138	146	55	B G	4

Push-fit socket/spigot

Adjustable 64° – 87½°						
Size mm	Code	A	B	C	Colour	Qty
82	SB38	124	127	57	B G	1

REAR ACCESS BRANCHES



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SY402	87½°	287	143	60	175	B G	4

2 boss upstands

Size mm	Code	Angle	A	B	C	D	Colour	Qty
82	SY34F	87½°	212	121	52	101	B G	6

Fixed


BOSS CONNECTOR



Size mm	Code	Angle	A	B	Colour	Qty
32	SA411	87½°	43	21	W B G	50
40	SA421	87½°	43	21	W B G	40
50	SA420	87½°	66	45	B G	40

Solvent weld with push-fit seal

LEVEL INVERT REDUCERS




Size mm	Code	A	B	C	Colour	Qty
110x82	SRM304	192	78	82	B G	20

Spigot/socket

Size mm	Code	A	B	C	Colour	Qty
160x110	SRM604	219	90	82	G	4

Spigot/socket

CONCENTRIC REDUCER




Size mm	Code	A	B	Colour	Qty
110-50	SE41	105	135	B G	18

Spigot to boss upstand

Size mm	Code	A	B	C	Colour	Qty
160	SRS604	168	68	20	G	6

Spigot to boss upstand

ADAPTOR



Size mm	Code	A	B	C	Colour	Qty
110	SA42	130	65	130	B	40


Soil to drain adaptor

Size mm	Code	A	B	C	Colour	Qty
110	SA110	58	25	34	B	10

Waste to drain adaptor


Solvent soil, PVCu

PIPE



110MM CO-EX SOIL					
Size mm	Code	Length	Colour	Qty	
110	SL403	3m	W B G	♥ 100	
110	SL404	4m	G	♥ 100	
160	SL603	3m	G	46	
160	SL604	4m	G	46	
Double spigot					

STRAIGHT COUPLINGS



Loose pipe socket					
Size mm	Code	A	B	C	Colour Qty
82	SE300	103	50	48	B G ♥ 30
110	SE400	109	61	48	W B G ♥ 8
160	SE600	190	107	77	G ♥ 4

Double solvent socket					
Size mm	Code	A	B	C	Colour Qty
82	SES301	93	44	82	G ♥ 50
110	SES401	102	50	124	B G ♥ 8
160	SES601	174	64	128	G 4


EXPANSION COUPLING



Solvent socket ring seal adaptor					
Size mm	Code	A	B	C	Colour Qty
110	SE409	105	20	52	B G 8

To accommodate thermal movement in both vertical and horizontal solvent pipework

SHORT RADIUS BENDS



Size mm	Code	Angle	A	B	C	Colour	Qty
110	SBS41	87 1/2°	162	168	50	G	♥ 4

Solvent socket/spigot

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SBS42	87 1/2°	149	149	47	B G	♥ 4
160	SBS62	87 1/2°	186	186	66	G	2

Double solvent socket

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SBS45	45°	76	76	52	B G	♥ 4
160	SBS65	45°	98	98	66	G	2

Double solvent socket

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SBS415	45°	76	89	52	B G	4

Solvent socket/spigot


LONG RADIUS BEND



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SBS40	87 1/2°	114	240	48	110	W B G	♥ 4

Solvent socket/spigot

OFFSET BENDS




Size mm	Code	Angle	A	B	C	Colour	Qty
110	SNE405	67 1/2°	76	61	60	W B G	4

Push-fit solvent socket

Size mm	Code	Angle	A	B	C	Colour	Qty
82	SNE300	67 1/2°	88	48	49	B G	30
160	SNE600	67 1/2°	178	182	96	G	140

Push-fit solvent socket.


EQUAL BRANCH



Size mm	Code	Angle	A	B	C	Colour	Qty
110	SYS460	45°	277	135	55	B G	4

Solvent sockets/spigot

EQUAL BRANCHES




Size mm	Code	Angle	A	B	C	Colour	Qty
110	SY466	45°	282	138	60	B G	4

Push-fit sockets/solvent socket

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SYS466	45°	274	135	55	B G	4
160	SYS666	45°	362	194	66	G	4

Triple solvent sockets

FIVE BOSS BRANCH



Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SYS405	87 1/2°	272	135	55	168	B G	♥ 4

Triple solvent socket

Size mm	Code	Angle	A	B	C	D	Colour	Qty
160	SYS601	87 1/2°	270	180	66	205	G	2

Triple solvent socket

Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SY415	87 1/2°	279	135	55	175	B G	♥ 4

Solvent socket/spigot

Solvent soil, PVCu

UNEQUAL BRANCHES

Size mm	Code	Angle	A	B	C	Colour	Qty
160	SYS644	45°	286	169	55	G	4

Size mm	Code	Angle	A	B	C	D	Colour	Qty
160	SYS664	87½°	234	132	52	118	G	4

DOUBLE BRANCH

Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SYS404	87½°	274	133	45	76	G	4

All solvent sockets, 4 boss upstands

CORNER BRANCH

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SYS411°	87½°	272	135	55	G	1

All solvent sockets. 1 boss upstand

BOSS PIPES

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SWS4135	45°	186	93	145	G	4

All solvent sockets. Three 50mm boss upstands

Size mm	Code	Angle	A	B	C	Colour	Qty
110x32	SWS415	87½°	170	85	52	W B G	4

Double solvent socket. One 32mm boss connection

Size mm	Code	Angle	A	B	C	Colour	Qty
110x40	SWS41	87½°	170	85	52	W B G	4

Double solvent socket. One 40mm boss connection

Size mm	Code	Angle	A	B	C	Colour	Qty
110x50	SWS42	87½°	170	85	52	B G	4

Double solvent socket. One 50mm boss connection

STRAP-ON-BOSS

Size mm	Code	Angle	A	B	Required hole size	Colour	Qty
32x110	SWS4150	90°	70	55	50	B G	40
40x110	SWS410	90°	70	62	50	B G	40
50x110	SWS420	90°	86	75	63	B G	30

CONDENSATE STRAP-ON-BOSS

Size mm	Code	Angle	A	B	Colour	Qty
21.5x110	SWS4C	90°	70	21.5	G	50

PATCH BOSS

Size mm	Code	A	B	Colour	Qty
32x82	SWS332	95	18	G	20
40x82	SWS340	95	23	G	20
50x82	SWS350	95	27	G	20

8-WAY COLLAR BOSS

Size mm	Code	A	B	C	D	Colour	Qty
110	SCB41	195	157	140	164	G	1

Solvent socket/spigot

Size mm	Code	A	B	C	D	Colour	Qty
110	SCBS41	184	146	140	164	G	1

Double solvent socket tail

Size mm	Code	A	B	C	D	Colour	Qty
110	SCBL41	532	146	140	164	G	1

Solvent socket/spigot with 350mm spigot tail

Solvent soil, PVCu

BOSS PIPES

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SWS40	90°	179	92	55	B G	4
160	SWS60	90°	200	100	66	G	4

Double solvent socket. 4 boss upstands, 1 drilled

Size mm	Code	Angle	A	B	C	Colour	Qty
110	SWS405		179	92	54	B G	4

Solvent socket/spigot. 4 boss upstands, 1 drilled


Size mm	Code	Angle	A	B	C	D	Colour	Qty
110	SWS406	90°	184	55	87	60	G	4

Push-fit/Solvent socket. 4 boss upstands.


Size mm	Code	Angle	A	B	C	Colour	Qty
160	SW60	90°	335	110	96	G	4

Solvent socket/spigot.

CONDENSATION TRAP

		Size mm	Code	A	B	C	Colour	Qty
		110	SCT4°	115	82	22	G	6
		With 21.5/22mm overflow connection						

ACCESS CAPS

Size mm	Code	A	B	Colour	Qty
82	SE30	114	35	B G	30
110	SE40	150	37	B G	30
160	SE62	195	40	G	15

With pressure plug

ACCESS PIPES

Size mm	Code	A	B	C	D	Colour	Qty
110	SFS41	150	75	56	154	W B G	4

Double solvent sockets, 3 boss upstands

Size mm	Code	A	B	C	D	Colour	Qty
160	SF611	287	144	138	223	G	2

Double solvent sockets

REAR ACCESS BEND

		Size mm	Code	Angle	A	B	C	Colour	Qty
		110	SBS420	87½°	131	128	54	B G	4
		Double solvent socket							

BOSS CONNECTORS

Size mm	Code	A	B	Colour	Qty
32	SA415	35	20	G	50
40	SA425	30	25	B G	50
50	SA435	58	28	G	50


Solvent weld with solvent weld joint


Size mm	Code	Angle	A	B	C	D	Colour	Qty
40	KBK25	90°	48	48	23	23	W B	20
50	KBK35	90°	59	50	20	28	W	10

Solvent weld

Size mm	Code	A	B	Colour	Qty
32	SA411	43	21	W B G	50
40	SA421	43	21	W B G	40
50	SA420	66	45	B G	40

CONCENTRIC REDUCERS

		<table><tr><th>Size mm</th><th>Code</th><th>A</th><th>B</th><th>Colour</th><th>Qty</th></tr><tr><td>110-50</td><td>SE41</td><td>105</td><td>135</td><td>B G</td><td>18</td></tr></table>	Size mm	Code	A	B	Colour	Qty	110-50	SE41	105	135	B G	18
Size mm	Code	A	B	Colour	Qty									
110-50	SE41	105	135	B G	18									
Spigot to boss upstand														

		<table><tr><th>Size mm</th><th>Code</th><th>A</th><th>B</th><th>C</th><th>Colour</th><th>Qty</th></tr><tr><td>160-110</td><td>SRS604</td><td>168</td><td>68</td><td>20</td><td>G</td><td>6</td></tr></table>	Size mm	Code	A	B	C	Colour	Qty	160-110	SRS604	168	68	20	G	6
Size mm	Code	A	B	C	Colour	Qty										
160-110	SRS604	168	68	20	G	6										
Spigot/Socket																

ECCENTRIC REDUCERS

Size mm	Code	A	B	Colour	Qty
82-50	SRM30	66	35	B G	90

Spigot tail

Size mm	Code	A	B	C	Colour	Qty
110-50	SRM402	48	25	19	B G	10

Solvent socket to boss upstand

VENT TERMINALS

Roof cowl/vent terminal

Size mm	Code	A	B	C	Colour	Qty
110	SVC1	200	98	70	W B G	10

Vent terminal

Size mm	Code	A	B	C	Colour	Qty
82	SV321	90	30	75	B G	30
110	SV42	117	34	95	W B G	60

Vent terminal

Size mm	Code	A	B	C	Colour	Qty
160	SV62°	160	71	25	G	20

200mm Push-fit soil, PVCu

Active drainage

PIPE

Size mm	Code	Length	Colour
200	SL806	6m	G
Double Spigot			

STRAIGHT COUPLINGS

Size mm	Code	Angle	A	B	Colour
200	063204M		217	106	G
Rubber ring/Rubber ring					
Size mm	Code	Angle	A		Colour
200	061204M		217		G
Slip coupler					
Size mm	Code	Angle	A		Colour
200	063208M		217		G
Rubber ring/Solvent cement					

SHORT RADIUS BENDS

Size mm	Code	Angle	A	B	C	Colour
200	070204M	45°	148	146	84	G
Socket/Spigot						
Size mm	Code	Angle	A	B	C	Colour
200	071204M	90°	207	205	85	G
Socket/Spigot						

EQUAL BRANCHES

Size mm	Code	Angle	A	B	C	Colour
200	030204M	45°	482	256	81	G
Socket/Spigot						
Size mm	Code	Angle	A	B	C	Colour
200	081204M	87°	410	119	86	G
Socket/Spigot						

UNEQUAL BRANCHES

Size mm	Code	Angle	A	B	C	Colour
200 x 160	031204M	45°	432	232	74	G
Socket/Spigot						

LEVEL INVERT REDUCERS

Size mm	Code	Angle	A	B	C	Colour
200 x 160	051404M		213	100	113	G
Socket/Spigot						

STUDOR P.A.P.A. (POSITIVE AIR PRESSURE ATTENUATOR)


Size mm	Code	A	B	C	D	E	F	G	H	I	Colour	Qty
75/110	8F-STU616-WHB	200	652	104	83	89	111	50	75	106	W	1
Installation recommendations												
5 - 10 floors		One unit on the base										
11 - 15 floors		One unit on the base, one halfway										
16 - 25 floors		One on base, one on 5th floor, one half way or remaining floors above 5th floor										
26 - 50 floors		Two units in series on the base, then one unit on every fifth floor up to the 25th floor, and then one every 10th floor										
51 or more		Please consult with manufacturer for further information										
Temperature range		- 20°C to + 60°C - 40°F to + 150°F					Volume Capacity					
Max. pressure rating		10,000 Pa (1m/40" H ₂ O) at 0 Pa or higher					Series assembly		(litres)			
							1 unit		3.785			
							2 units		7.570			
							3 units		11.355			
							4 units		15.140			

STUDOR MAXI-VENT WITH CONNECTOR

Size mm	Code	A	B	C	D	E	F	G	H	I	Colour	Qty
75/110	8F-STU616-WHB	200	652	104	83	89	111	50	75	106	W	1
Performance parameter												
Temperature range		- 40°C to + 60°C (CE) - 40°F to + 150°F (ASSE)					Air flow capacity		Branch		Stack	
Opening pressure		-70 Pa (-0.010 PSI)					Europe		32 l/s		32 l/s	
Max. pressure rating tightness		10,000 Pa (1m/40" H ₂ O) at 0 Pa or higher					AU/NZ		32 l/s / 1728 FU		32 l/s / 125 FU	
							USA		1 to 160 DFU		72 to 500 DFU	

STUDOR MINI-VENT WITH CONNECTOR





Size mm	Code	A	B	C	D	E	F	G	Qty
32-63	49017	70	67	47	67	31.9	33	64	1

Performance parameter

Temperature range	-20°C to +60°C (CE) -40°F to +150°F (ASSE)
Opening pressure	-70 Pa (-0.010 PSI)
Max. pressure rating tightness	10,000 Pa (1m/40" H ₂ O) at 0 Pa or higher

Air flow capacity

	Branch	Stack
Europe	7.5 l/s	7.5 l/s
AU/NZ	7.5 l/s / 94 FU	7.5 l/s / 7 FU
USA	1 to 160 DFU	8 to 24 DFU

Accessories

CLIPS



Socket clip					
Size mm	Code	A	B	Colour	Qty
110	SC41	152	101	B G	50
160	SC61	240	121	G	50

PVC coated mild steel, includes 6x20mm nut and bolt



Barrel clip collar				Colour	Qty
Size mm	Code				
1000	SC621			G	25

Converts socket clip to pipe clip (3x110mm or 2x160mm)



Pipe clip					
Size mm	Code	A	B	Colour	Qty
82	SC35	117	70	B G	20

PVCu



Pipe clip					
Size mm	Code	A	B	Colour	Qty
82	SC35	117	70	B G	20

PVCu



Extension backplate					Qty
Code	A	B	Colour		
RT200	104	45	W B G BR		50

PVCu
For use with RC251/2, RCE2 and RC32 pipe clips



Drive-in spike					
Size mm	Code	A	B	Colour	Qty
	RSS1°	115	58 19	G	50

For use with drive-in spike or backplate.



Backplate					Qty
Code	A	B	Colour		
RCB300	48	31	W B G BR		100

For use with SC355

CLIPS



Extension Bracket					Qty
Code	A	B	Colour		
RT250	243	114	B G		20



Cover plate					Qty
Code	A	B	Colour		
RT2501	111	35	B G		1

For use with RT250



Pipe clip					Qty
Code	A	B	Colour		
RPC1	137	111	B G		20




Socket clip					Qty
Code	A	B	Colour		
RSC1	141	119	B G		1



Size mm	Code	A	B	C	Colour	Qty
82	SV31*	51	94	25	B	100
110	SV43	57	130	25	W B G	35

PVCu for solvent joint to pipe *Available in black rubber only.

WEATHERING SLATES



Size mm	Code	A	B	Colour	Qty
400	SAS40	400	400	G	5

Flat



Size mm	Code	A	B	Colour	Qty
450	SAS45	450	450	G	5
610	SAS61	610	610	G	5

Inclined. Aluminium to rubber

WC connectors/Modern

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

STRAIGHT



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS2	97 – 108	99 – 105	0.16	43	52	15

Known as the No.2 – the plumbers favourite
This connector is for new style pans only




EXTENDED STRAIGHT



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS4	97 – 108	99 – 105	0.19	45	105	70


LONG ADJUSTABLE STRAIGHT



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKLAS1	97 – 108	99 – 105	0.46	40	285	255

Can be cut to suit
This connector is for new style pans only

STRAIGHT – INCLUDING VENT BOSS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKSB4	97 – 108	99 – 105	0.22	42	104	70


40mm vent boss

18MM OFFSET



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK02	97 – 108	99 – 105	0.17	45	70	20

40MM OFFSET



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK04	97 – 108	99 – 105	0.19	43	85	43

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

MULTICLIK – FLEXIBLE STRAIGHT



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKC2	97 – 108	99 – 105	0.37	50	170	120

Extends from 225 to 550mm
Superior quality hose retains its position whatever shape is required
Ideal when installing back to the wall, floor standing pans


MULTICLIK 90° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKC2B90	97 – 108	99 – 105	0.57	50	270	110

Extends from 375 to 710mm
Superior quality hose retains its position whatever shape is required
Converts a 'P' trap into an 'S' trap with adjustment for final connection

MULTICLIK 90° BEND INCLUDING BOSS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKC2BB90	97 – 108	99 – 105	0.59	50	265	105

Extends from 405 to 740mm
Superior quality hose retains its position whatever shape is required
Converts a 'P' trap into an 'S' trap with adjustment for final connection
To be installed in a vertical position

14° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB114	97 – 108	99 – 105	0.19	43	80	30

45° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB45	97 – 108	99 – 105	0.19	43	100	60

Ideal for corner installations

104° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB21104	97 – 108	99 – 105	0.24	60	110	34

WC connectors/Modern

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

90° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKBB2190	97 – 108	99 – 105	0.30	60	115	80

90° BEND – INCLUDING VENT BOSS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKBB2190	97 – 108	99 – 105	0.31	60	110	65

40mm vent boss
Must be used in a vertical position if boss is being used

90° BEND – TALL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKBB3190	97 – 108	99 – 105	0.36	43	200	90

90° BEND – INCLUDING BOSS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKBB3190	97 – 108	99 – 105	0.35	43	200	70

Includes 40mm compression boss
Must be used in a vertical position if boss is being used

90° SPACE SAVER BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKBBAR90	97 – 108	99 – 105	0.38	34	255	91

Ideal when replacing old BS1213 'S' trap pans
Can be cut to suit both horizontally and vertically

RIGID 18MM OFFSET



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKR02	97 – 108	99 – 105	0.20	35	80	35

40mm vent boss

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

RIGID 14° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKRB14	97 – 108	99 – 105	0.20	40	105	40

RIGID 90° BEND



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKRB90	97 – 108	99 – 105	0.33	37	210	50

Adjustable length: remove the fined seal and cut with a fine tooth saw

RIGID STRAIGHT



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKRS2	97 – 108	99 – 105	0.20	37	75	30

RIGID 100MM OFFSET



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK0100	97 – 108	99 – 105	0.26	40	207	26

Extension length: 15mm


EXTENDED STRAIGHT FOR 3½” SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS7	97 – 108	88 – 92	0.17	41	70	15

Extension length: 15mm

18MM OFFSET FOR 3½” SOIL




Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK07	97 – 108	88 – 92	0.15	34	77	30

WC connectors/Modern

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

18MM OFFSET OLD BS1213 PANS TO OVERSIZE SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK01S	97 – 108	105 – 108	0.18	45	76	20

14° BEND FOR OVERSIZE SOIL




Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB114S	97 – 108	105 – 108	0.20	43	80	35

90° BEND FOR OVERSIZE SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB2190S	97 – 108	105 – 108	0.32	60	115	80

STRAIGHT



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS1	108 – 114	99 – 105	0.16	44	67	15

Known as the No.1 – the plumbers favourite
This connector is for old style pans only – for new pans use an MKS2 (see page 24)

STRAIGHT OLD BS1213 SYPHONIC PANS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS1A	108 – 114	99 – 105	0.17	40	70	15

18MM OFFSET OLD BS1213 PANS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK01	108 – 114	99 – 105	0.17	45	70	25

WC connectors/Old

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

90° TIGHT KNUCKLE BEND OLD BS1213 PANS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB21	108 – 114	99 – 105	0.24	45	80	80

Includes 40mm compression boss
Must be used in a vertical position if boss is being used

90° TIGHT KNUCKLE BEND OLD BS1213 PANS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB22	108 – 114	99 – 105	0.24	45	80	75

Ideal when replacing old BS1213 'S' trap pans
Can be cut to suit both horizontally and vertically

STRAIGHT 3½" SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS3	108 – 114	88 – 92	0.16	41	70	10

40mm vent boss

18MM OFFSET OLD BS1213 PANS TO 3½" SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK03	108 – 114	88 – 92	0.15	37	78	30

STRAIGHT 3½" SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS10	108 – 114	74 – 77	0.16	35	86	12

Adjustable length: remove the fined seal and cut with a fine tooth saw

90° TIGHT KNUCKLE BEND OLD BS1213 PANS TO OVERSIZE SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB21S	108 – 114	105 – 108	0.25	45	75	60

WC connectors – Stainless steel / Ancillaries


PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm

STRAIGHT UNDERSIZE SPIGOTS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS5	76 – 95	99 – 105	0.22	45	55	15

EXTENDED STRAIGHT UNDERSIZE SPIGOTS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKS8	76 – 95	99 – 105	0.26	42	110	70

Extension length: 59mm

18MM OFFSET UNDERSIZE SPIGOTS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MK05	76 – 95	99 – 105	0.24	45	72	22

14° BEND UNDERSIZE SPIGOTS



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB514	76 – 95	99 – 105	0.26	42	85	40

14° BEND UNDERSIZE SPIGOTS TO 3½" SOIL



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B	C
MKB614	76 – 95	88 – 92	0.25	37	90	40

SOIL PIPE EXTENSION FOR 4" SOIL



Code	Soil pipe inner diameter (mm)	Weight	A	B
MKEA	99 – 105	0.24	50	202

Can be cut to required length
Ideal when removing 4" cast iron, clay and PVCu

PIPE: 1: Standard 99-105mm 2: Cast Iron 88-92mm 3: Old 74-77mm 4: Copper 105-108mm


SOIL PIPE EXTENSION FOR 3" SOIL



Code	Soil pipe inner diameter (mm)	Weight	A	B
MKEB	88 – 92	0.22	50	202

Can be cut to required length
Ideal when removing 3½" cast iron


SOIL PIPE EXTENSION FOR 3" SOIL



Code	Soil pipe inner diameter (mm)	Weight	A	B
MKEG	74 – 77	0.21	42	210

Can be cut to required length
Ideal when removing 3" cast iron

RIGID SOIL PIPE EXTENSION



Code	Pan spigot outer diameter (mm)	Soil pipe inner diameter (mm)	Weight	A	B
MKREXT	97 – 108	99 – 105	0.23	35	264

Adjustable length: remove the fined seal and cut with a fine tooth saw

FLUSH PIPE CONNECTOR



Code	Soil pipe inner diameter (mm)	Weight	A	B
MKFPC1	–	0.02	65	26

MULTILINK




Code	Soil pipe inner diameter (mm)	Weight	A
MKL1	99 – 105	0.04	52.5

For connecting 2 or more pan connectors
Suitable for sleeving the fins of all 99 – 105mm Multikwik outlets

WC manifold system


BRANCH



Size mm	Code	A	B	C	Colour	Qty
110x90	SM41W	214	50	116	W	10

Solvent sockets


ADJUSTABLE WC BEND



Size mm	Code	Angle	A	B	C	D	Colour	Qty
90	SM42W*	50-90°	108	134	75	60	W	15

50mm boss upstand
Pan socket to be trimmed to suit WC spigot length


ADJUSTABLE SPIGOT BEND



Size mm	Code	Angle	A	B	Colour	Qty
90	SM43W	50-90°	119	75	W	15

50mm boss upstand


WC CONNECTOR



Size mm	Code	A	B	C	D	Colour	Qty
90	SM44W*	117	134	46	80	W	30

50mm boss upstand
Pan socket to be trimmed to suit WC spigot length


EXTENSION PIPE



Size mm	Code	A	B	Colour	Qty
90	SM45W	96	46	W	50

300mm
For use with SM43 only

WC SEAL AND CAP




83-114mm outlet		A	B	Colour	Qty
Size mm	Code	141	24	W	70

For use with SM42 and SM44

WC manifold systems


For use in sanitary pipework systems in schools, hospitals, public and commercial buildings, the manifold system allows ranges of toilets to be connected to a horizontal float above floor level and eliminates the need for specially fabricated fittings.

The components are suitable for installation in a duct, or for fitting on the surface of the wall directly behind the pan. Where the manifold is fitted directly behind the range of toilets, the minimum distance between the end of the WC spigot and the face of the wall is 150mm.




PVCu floor outlets

TRAPPED FLOOR GULLIES




Size mm	Code	A	B	C	D	Colour	Qty
50	SFG42AS	117	164	145	116	G	8
Solvent outlet. 90mm adjustable water seal							
Size mm	Code	A	B	C	D	Colour	Qty
82	SFG43AS	117	164	175	100	G	8
Solvent outlet. 75mm adjustable water seal							

PVC FLOOR TILE



Code	A	B	C	Colour	Qty
SGG3	150	150	7	G	10
For use with SFG42AS and SFG43AS only					

STAINLESS STEEL TILE GRATE AND COVER



Code	A	B	C	Colour	Qty
150x150 SGG4	150	150	7	NU	40
Grade 304 stainless steel					

Ancillary items

VENT TERMINAL



Size mm	Code	A	B	Colour	Qty
50	RV225	55	18	W B G	30


SPARE RING SEALS



'T' ring				
Size mm	Code	Colour	Qty	
82	SR82T	B	5	
110	SR110T	B	5	
160	SR160T	B	5	
To BS EN 681/1				


PVCu flat roof outlets

SPIGOT TAIL




Size mm	Code	A	B	C	D	Colour	Qty
82	RV637	280	157	214	130	G	1
110	RV369	280	157	214	122	G	1
160	RV482	380	170	250	148	G	1

BALCONY - FULL FLAT GRATING, SOLVENT SOCKET TAIL



Size mm	Code	A	B	Colour	Qty
82	RV195	355	165	G	1
110	RV196	355	140	G	1

Typical installation detail




NB: It is important to prevent upthrust on the vertical rainwater pipe due to thermal movement from breaking the joint between the outlet and roof finish. Thermal movement can be accommodated by anchoring a push-fit socket with a socket bracket and allowing a 10mm expansion gap between spigot end and socket depth. A maximum of 4m between expansion joints should be allowed for.

It may be necessary to provide a warning pipe to indicate blockage on internal rainwater systems. For more details refer to BS EN 12056 - 3

Traps

BOTTLE – STANDARD





Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032	White	75	0.15	180 x 74 x 125
40	B040	White	75	0.18	184 x 78 x 127


BOTTLE – RESEALING

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032R	White	75	0.16	180 x 74 x 125
40	B040R	White	75	0.19	184 x 78 x 127

Resealing function to prevent loss of water seal

BOTTLE – ADJUSTABLE






Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032A	White	75	0.19	195 x 74 x 125
40	B040A	White	75	0.22	195 x 78 x 127

Adjustable inlet for installation flexibility
Min height: 195mm; max height: 300mm


BOTTLE – ADJUSTABLE / RESEALING



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032RA	White	75	0.20	195 x 74 x 125
40	B040RA	White	75	0.23	195 x 78 x 127

Adjustable inlet for installation flexibility
Resealing function to prevent loss of water seal
Min height: 195mm; max height: 300mm

BOTTLE – ANTI-VAC


Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032V	White	75	0.16	180 x 74 x 125
40	B040V	White	75	0.19	186 x 84 x 125

Resealing function to prevent loss of water seal

Anti-vac allows air into the waste pipes to prevent self-syphonage of the traps

water seal and gurgling


BOTTLE – COMPACT

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032S	White	75	0.12	136 x 75 x 85
40	B040S	White	75	0.13	152 x 81 x 100

Use when connecting into flat bottomed appliances that discharge into a gully


BOTTLE – SLIMLINE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	BS032	White	75	0.15	182 x 71 x 112

Space saving
Adjustable inlet for installation flexibility
Minimum height: 195mm; max height 300mm


STRAIGHT THROUGH ADJUSTABLE




Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	ST032	White	75	0.24	270 x 33

Unique slim-line design, saving space
Adjustable telescopic outlet for installation flexibility
Easy to clean and maintain

BOTTLE – ADJUSTABLE

		Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
		32	B032ACR	Chrome	75	0.45	195 x 74 x 125
High quality mirror chrome finish Includes 400mm x 32mm chromed pipe Adjustable inlet for installation flexibility Min height: 195mm; max height: 300mm							

BOTTLE – ADJUSTABLE / RESEALING




Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
32	B032RACR	Chrome	75	0.25	195 x 74 x 125
40	B040RACR	Chrome	75	0.29	225 x 80 x 130

Resealing function to prevent loss of water seal
High quality mirror chrome finish
Adjustable inlet for installation flexibility
Min height: 195/225mm; max height: 300/327mm

Traps


UNIVERSAL ALL IN ONE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
32	SP032	White	75	0.19	267 x 140 x 85 x 55
40	SP040	White	75	0.22	285 x 140 x 80 x 65

Adjustable inlet for installation flexibility
Multi position outlet adjusts 360° providing installation flexibility
Use as either an 'S' or 'P' trap


RUNNING



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
32	RP032	White	75	0.16	135 x 130 x 115 x 60
40	RP040	White	75	0.20	160 x 145 x 130 x 65
50	RP050X	White	75	0.25	185 x 165 x 160 x 75

Use to trap a range of appliances


'P' TRAP



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
32	P032	White	75	0.11	140 x 125 x 115 x 60
40	P040	White	75	0.14	165 x 145 x 130 x 65
50	P050	White	75	0.22	190 x 165 x 160 x 75

Use for horizontal pipework


'P' TRAP – ADJUSTABLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
32	P032A	White	75	0.15	220 x 135 x 115 x 60
40	P040A	White	75	0.20	245 x 145 x 130 x 65

Adjustable inlet for installation flexibility
Min height: 220mm; max height: 270mm


'S' TRAP



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
32	S032	White	75	0.14	160 x 110 x 55
40	S040	White	75	0.17	160 x 130 x 65

Use for vertical pipework


TUBULAR SWIVEL



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	SWM040A	White	75	0.25	255 x 150 x 127 x 65

Adjustable inlet for installation flexibility
Inlet and outlet swivels to aid easy connection to pipes even in confined spaces


SHOWER – COMPACT



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40 outlet	S5040C	White	50	0.18	92 x 150 x 70

Chrome waste
70mm flange
High flow rate: 0.76 l/s


SHOWER – COMPACT



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40 outlet	S5040W	White	50	0.18	92 x 150 x 70

White waste
70mm flange
High flow rate: 0.76 l/s

SHOWER – RESEALING



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40 outlet	S5040CR	White	50	0.18	92 x 150 x 70

Chrome waste
Eliminates self-syphonage and gurgling through resealing device
70mm flange
High flow rate: 0.76 l/s

Traps

BATH – ONE PIECE

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40	P1940	White	19	0.08	70 x 75 x 145

For low level floors where a deeper water seal trap doesn't fit
For appliances that discharge into a gully

BATH – LOW LEVEL

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	P5040	White	50	0.15	140 x 110 x 89 x 172

Rodding point for cleaning

BATH – LOW LEVEL ANTI-VAC

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	P5040V	White	50	0.21	135 x 105 x 89 x 230

Anti-vac allows air into the waste pipes to prevent self-syphonage of the traps water seal and gurgling
Rodding point for cleaning

BATH – SWIVEL 'P' LOW LEVEL INLET

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	P040L	White	75	0.13	125 x 150 x 127 x 65

BATH – STANDARD

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	P6040	White	60	0.17	140 x 110 x 98 x 220

Rodding point for cleaning

BATH – LOW LEVEL

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D x E
40	P5040F	White	50	0.37	355 x 325 x 140 x 115 x 175

Flexible overflow pipe for ease of installation
Plug tidy overflow to retain plug when not in use

BATH – STANDARD

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D x E
40	P6040F	White	60	0.39	410 x 375 x 140 x 115 x 220

Flexible overflow pipe for ease of installation
Plug tidy overflow to retain plug when not in use

ANTI-VAC GURGLEMMASTER

Size (mm)	Code	Colour	Weight	Dimensions (mm) A x B x C
32	WV032	White	0.05	80 x 90 x 39
40	WV040	White	0.06	90 x 90 x 40

Anti-vac allows air traps into the waste pipe to prevent gurgling and self-syphonage of the traps water seal
Quick installation with simple multi-fit in-line assembly

ANTI-SYPHON UNIT

Size (mm)	Code	Colour	Weight	Dimensions (mm) A x B
32	WW150	White	0.05	57 x 61
40	WW151	White	0.05	60 x 61

To BS EN 12380
Anti-vac allows air into the waste pipe to prevent gurgling and self-syphonage of the traps water seal
Use with any BS EN 1566/5255 solvent weld sockets


WASHING MACHINE

Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	PWM040	White	75	0.29	560 x 160 x 140 x 65

Includes 500mm standpipe, retaining clips, screws and raw plugs

Traps


UTILITY 'P' COMPACT – SINGLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40	PWM040T	White	75	0.21	190 x 145 x 270

Nozzle for connecting a washing machine or dishwasher


ADJUSTABLE UTILITY 'P' – SINGLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	PWM040S	White	75	0.20	250 x 215 x 145 x 65

Adjustable inlet for installation flexibility
For connecting a washing machine or dishwasher
Non-return valve to prevent backflow in nozzle
Min height: 250mm; max height: 310mm


ADJUSTABLE UTILITY 'P' – DOUBLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	PWM040D	White	75	0.23	250 x 215 x 145 x 65

Adjustable inlet for installation flexibility
For connecting two appliances
Non-return valve to prevent backflow in nozzle
Min height: 250mm; max height: 310mm


ADJUSTABLE UTILITY 'S' – SINGLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	SWM040S	White	75	0.24	250 x 217 x 125 x 65

Adjustable inlet for installation flexibility
For connecting a washing machine or a dishwasher
Non-return valve to prevent backflow in nozzle
Min height: 250mm; max height: 310mm


ADJUSTABLE UTILITY 'S' – DOUBLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D
40	SWM040D	White	75	0.26	250 x 220 x 125 x 65

Adjustable inlet for installation flexibility
For connecting a washing machine and dishwasher
Non-return valve to prevent backflow in nozzle
Min height: 250mm; max height: 330mm


SPACE SAVER KIT



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40	SBK040D	White	75	0.34	330 x 145 x 375

Single bowl, double nozzle
Flexible installation with full width and height adjustment


1½ BOWL KIT – SINGLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C x D x E
40	XS040S	White	75	0.36	410 x 140 x 395

Flexible installation with full width and height adjustment


DOUBLE BOWL KIT – SINGLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40	DBK040S	White	75	0.42	410 x 140 x 395

Flexible installation with full width and height adjustment


EXTENDED DOUBLE BOWL KIT – DOUBLE NOZZLE



Size (mm)	Code	Colour	Water Seal Depth (mm)	Weight	Dimensions (mm) A x B x C
40	DBKDS040	White	75	0.49	410 x 140 x 610

Flexible installation with full width and height adjustment


TRAP HEIGHT ADJUSTER – SINGLE NOZZLE



Size (mm)	Code	Colour	Weight	Dimensions (mm) A x B x C
40	WA040S	White	0.07	195 x 150 x 70

For connections to a washing machine or dishwasher
Non-return valve prevents backflow in nozzle

TRAP HEIGHT ADJUSTER – DOUBLE NOZZLE




Size (mm)	Code	Colour	Weight	Dimensions (mm) A x B x C
40	WA040D	White	0.10	195 x 150 x 78

For connections to a washing machine or dishwasher
Non-return valve prevents backflow in nozzle

Solid wall drainage systems

PIPE




Size mm	Code	Length	Colour	Qty
82	UL3057	5.7m	O	156*
110	UL403	3m	O	100
110	UL406	6m	O	100
160	UL606	6m	O	46

Double spigot with chamfer each end

Size mm	Code	Length	A	B	Colour	Qty
82	UP3057	5.7m	100	76	O	156*
110	UP403	3m	128	70	O	100
160	UP603	3m	182	107	O	46
110	UP406	6m	128	70	O	100
160	UP606	6m	182	107	O	46

Push fit socket


SLOTTED PIPE



Size mm	Code	Length	A	B	Colour	Qty
110	UPP406	6m	128	70	O	1

Push fit socket

STRAIGHT COUPLINGS



Push fit polypropylene coupling

Size mm	Code	A	B	Colour	Qty
110	UE407	102	50	O	20

(Supplied in U.V. resistant polythene bags)

Push fit coupling

Size mm	Code	A	B	Colour	Qty
110	UE406	128	61	O	8
160	UME15C	170	83	O	4

Push fit slip coupling

Size mm	Code	A	Colour	Qty
82	UE305	104	O	100*
110	UE405	128	O	8
160	UME16C	170	O	4


STRAIGHT COUPLING



Loose pipe socket


Size mm	Code	Length	A	B	Colour	Qty
110	UE400	109m	61	48	O	8
160	UE600	190m	107	77	O	4

SHORT RADIUS BENDS



Size mm	Code	Angle	A	B	Colour	Qty
82	UB31	90°	117	120	O	100*
110	UB41	87½°	175	182	O	4
160	UFB61	87½°	236	232	O	1
82	UB35	45°	75	73	O	100*
110	UB45	45°	145	125	O	4
160	UFB65	45°	130	118	O	1
110	UB430R	30°	89	82	O	4
160	UB69	30°	160	150	O	1
110	UB420	20°	102	81	O	1
160	UB68	15°	150	110	O	1
110	UB410	10°	98	75	O	1

Push-fit socket/spigot



Size mm	Code	Angle	A	B	Colour	Qty
110	UB411	87½°	158	158	O	4
160	UMB19C	87½°	200	200	O	1
110	UB455	45°	95	95	O	4
160	UMB14C	45°	115	115	O	1
110	UB4300R	30°	80	80	O	4
160	UMB13C	30°	105	105	O	1
110	UB4200	20°	102	81	O	1
160	UMB11C	15°	95	95	O	1
110	UB4100	10°	98	76	O	1

Double push-fit socket


ADJUSTABLE BENDS



Size mm	Code	Angle	A	B	Colour	Qty
110	UB47	21 – 90°	210	205	O	4
160	UB67	15 – 90°	285	275	O	2

Socket should be solvent welded

MULTIFLEX BENDS



Size mm	Code	Angle	A	B	Colour	Qty
110	USB110	0 – 90°	205	205	O	1

Single socket

Size mm	Code	Angle	A	B	Colour	Qty
110	UDSB110	0 – 90°	205	205	O	1

Double socket

MECHANICAL BEND




Size mm	Code	Angle	A	B	Colour	Qty
110	UB47M	5 – 30°	200	177	O	1

Solid wall drainage systems

Inspection chambers


LONG RADIUS BEND



Size mm	Code	Angle	A	B	R	Colour	Qty
110	UBL488	87½°	310	360	270	O	4


Socket/socket

EQUAL BRANCHES



Size mm	Code	Angle	A	B	C	Colour	Qty
110	UY401	87½°	300	150		O	4
160	UY601	87½°	400	200		O	2
82	UY36	45°	231	155	155	O	100*
110	UY46	45°	320	205	205	O	4
160	UY63	45°	400	280	280	O	2


Socket/spigot



Size mm	Code	Angle	A	B	C	Colour	Qty
110	UY400	87½°	300	150		O	4
160	UMY13C	87½°	400	200		O	2
110	UY466	45°	325	215	200	O	4
160	UMY11C	45°	400	280	280	O	2


All socket

UNEQUAL BRANCHES



Size mm	Code	Angle	A	B	C	Colour	Qty
160 x 110	UY64	87½°	340	180	126	O	2
160 x 110	UY66	45°	357	245	254	O	2


Socket/spigot



Size mm	Code	Angle	A	B	C	Colour	Qty
160 x 110	UMY12C	87½°	340	180	252	O	2
160 x 110	UMY10C	45°	316	232	236	O	2

All socket


ACCESS BEND



Size mm	Code	Angle	A	B	C	Colour	Qty
110	UB42	87½°	172	174	80	O	4


With rear access, socket/spigot
Fitted with a twist and lock access cap which can be secured with a No. 8 screw

RODDING POINT



Size mm	Code	Angle	A	B	C	Colour	Qty
110	URP1	45°	164	68	70	O	10


A15 loading. Black cover with four screw fixings and seal



Size mm	Code	Angle	A	B	C	Colour	Qty
160	URP2C	45°	190	92	89	O	4

A15 loading. Aluminium cover with two screw fixings


SQUARE RODDING POINT COVER (SPARE)



Size mm	Code	A	B	Colour	Qty
110	URPFSQ	163	18	B	10

For use with URP1


ACCESS CAP



Size mm	Code	A	B	Colour	Qty
110	UE42	130	30	O	50
160	UE62	195	40	O	15

Solvent socket


PRESSURE PLUG



Size mm	Code	A	B	Colour	Qty
110	UE43	110	30	O	135
160	UE64	160	30	O	30

Push fits into plain end of pipe

450MM INSPECTION CHAMBER BASES




Size mm	Code	A	B	C	D	Colour	Qty
110	UCC3	245	608	608	50	B	1

Supplied with 4 blanking plugs. Max invert depth 1.2m (when used with UCR2 riser). 245mm high. All 110mm connections.

The 'D' dimension relates to the height of side branches above invert of main channel

Inspection chambers

450MM INSPECTION CHAMBER BASES




Size mm	Code	A	B	C	D	Colour	Qty
110/160	UCC5	80	75	490	192	B	1

The A and B dimensions relate to the height of side branches above invert level of main channel.

Max invert depth 4m (when used with UCR3 riser)

All socket connections. 400mm high, 110 and 160mm, connections.

CHAMBER RISER




Size mm	Code	A	B	Colour	Qty
450	UCR2	390	450	B	1

Push fit ring seal joint into chamber base. 430mm high, includes one 450mm seal.

For use with UCC3/5 for invert depths up to 1.2m

DEEP INSPECTION CHAMBER




Size mm	Code	A	B	Colour	Qty
110	UCC3D	608	608	B	1

Max invert depth 4m (when used with UCR3 riser)

All socket connections.

655mm high

DEEP INSPECTION CHAMBER RISER



Size mm	Code	A	B	Colour	Qty
450	UCR3	410	488	B	1


For use with UCC3D or UCC5 when invert depth is greater than 1.2m.

Max invert depth 4m

480mm high

Includes one 450mm seal

REDUCED ACCESS RING




Size mm	Code	A	B	Colour	Qty
450	UCLRR	60	455	B	1

Provides 350mm restricted opening. Snap lock connection to the frame of the UCL35PP and UCL35SQ.

For use with UCL35PP


CAST IRON COVER AND FRAME



Size mm	Code	A	B	C	Colour	Qty
450	UCL35	517	490	40	B	1

3.5 tonnes. Domestic driveway loading

POLYPROPYLENE COVER AND FRAME




Size mm	Code	A	B	C	Colour	Qty
450	UCL35PP	547	494	70	B	1

3.5 tonnes. Domestic driveway loading

Size mm	Code	A	B	C	Colour	Qty
450	UCL35SQ	547	494	70	B	1

3.5 tonnes. Domestic driveway loading


DUCTILE IRON LID AND CAST IRON FRAME



Size mm	Code	A	B	C	Colour	Qty
450	UCL125	547	492	48	B	1

12.5 tonnes


CHAMBER RISER CLIP



Code	A	B	Qty
UCC10	19	200	10

For use with UCR2 riser

DEEP INSPECTION CHAMBER RISER CLIP




Code	A	B	Qty
UCC10D	19	204	10

For use with UCR3 riser.

Zintec coated, supplied in packet of 10.

Used to connect chamber to riser and riser to riser.


INSPECTION CHAMBER INSERTS



Code	A	B	C	D	Colour	Qty
Left hand UCB1	425	159	171	167	B	1
Right hand UCB2	425	159	167	171	B	1

For use with the UCC5 inspection chamber

SPARE BLANKING PLUG



Size mm	Code	A	B	C	Colour	Qty
110	UCP1	117	110	40	B	70
160	UCP2	165	160	60	B	1

Black polypropylene

For use with UCC3/5

SPARE RING SEAL




Size mm	Code	Colour	Qty
450	SR450	B	1

For use with UCR2/3

Inspection chambers

Solid wall drainage systems


LEVEL INVERT INSPECTION CHAMBER



Size mm	Code	A	B	C	Colour	Qty
250	UCC7	380	420	600	O	1

Maximum invert depth – 600mm
All 110mm socket connections


DOUBLE BRANCH CHAMBER BASE



Size mm	Code	A	B	C	Colour	Qty
250	UAC44	344	275	170	O	1

45° equal connections
Includes two socket plugs and profiled insert
Maximum invert depth – 600mm


BOTTOM OUTLET CHAMBER BODY



Size mm	Code	A	B	C	Colour	Qty
250	UAC02	428	415	120	O	1

Maximum invert depth to side connections – 600mm
90° equal connections
4 x 110mm upstands, 3 open connections


CHAMBER RISER



Size mm	Code	A	B	Colour	Qty
250	UAR1	375	250	O	1

For use with UAC44 & UAC02.
Includes 250mm seal.


LIFTING HANDLE



Size mm	Code	Length	A	Colour	Qty
40	KP204W	4	40	W	10

For use with UAC44

INSPECTION CHAMBER LID & FRAME



Size mm	Code	A	B	C	Colour	Qty
250	UCL2	280	50	20	B	1

PVCu (A15 loading)


SPARE RING SEAL



Size mm	Code	Colour	Qty
250	SR250	B	1

Optional for UCL2 PVCu lid


SQUARE LID & FRAME



Size mm	Code	A	B	C	Colour	Qty
250	UCL3	318	20	78	B	1

A15 loading


STRAIGHT DOUBLE SPIGOT OPEN CHANNEL



Size mm	Code	A	B	C	Colour	Qty
110	UCC4	1500	610	445	O	1

Double spigot, keyed for sand/cement benching
1.5m long, with 600mm opening

LONG RADIUS OPEN CHANNEL BEND



Size mm	Code	Angle	A	B	C	Colour	Qty
110	UCB48L	87½°	310	360	270	O	1

Double spigot, keyed for sand/cement benching

Gullies

SPARE GULLY GRID



Size mm	Code	A	B	Colour	Qty
110	UG46	148	12	B	20

For use with UG40 gully and UG45, UG47 & UG48 gully hoppers


SPARE GULLY BACK PLATE



Size mm	Code	A	B	C	Colour	Qty
110	UG49	150	80	16	B	20

For use with UG40 gully and UG47 gully hoppers

INLET RAISING PIECES




Size mm	Code	A	B	Colour	Qty
110	UWS43	148	156	O	4

2 x 82mm upstands

Size mm	Code	A	B	C	Colour	Qty
110	UW401	181	125	20	O	4

Solvent socket/spigot, four 50mm boss upstands, one open

YARD GULLY



Size mm	Code	A	B	C	D	Colour	Qty
110	UYG40	634	315	392	238	B	1

Black high density polyethylene with spigot outlet and removable rodding access plug

GRATING AND FRAME FOR YARD GULLY



Size mm	Code	A	B	C	Colour	Qty
400	UYG42	400	320	75	B	1

Cast iron with hinged grating
B125 loading (12.5 tonne test load) suitable for car park areas

ADAPTORS



Size mm	Code	A	B	C	Colour	Qty
110	UCA40	120	110	130	B	1

Socket/socket to suit thin wall clayware spigot pipe

Size mm	Code	A	B	C	Colour	Qty
110	UCA41	120	110	138	B	1

Socket/socket to suit thick wall clayware pipe


ANTI-FLOOD VALVE



Size mm	Code	A	B	C	Colour	Qty
110	USW130	175	52	69	B	1
160	USW140	225	100	92	B	1

Double flap

Installation Guidance



Ventilation of soil stacks

Fundamentally, an efficient drainage system design is about managing the mix of air and water. More precisely, it is about managing the air pressure regime within the boundaries that maintain a water seal in the trap. Marley offer 3 different product solutions to manage this.


1. Secondary Ventilation

Traditional drainage design incorporates the installation of a secondary ventilation stack and branch pipework system alongside the main soil and waste stacks to ensure this air pressure is maintained.

Soil stack capacity

The capacity of a soil stack can be increased by the installation of a secondary ventilated stack. The following information is taken from tables 11 & 12 of BS EN 12056-2: 2000 which illustrates this increase.

	Stack size (mm)	Secondary vent (mm)	Maximum capacity (l/s) Swept entries
Primary ventilated stack	82	-	2.6
	110	-	5.2
	160	-	12.4
Secondary ventilated stack	82	50	3.4
	110	50	7.3
	160	80	18.3



2. Single Stack System with Stack-Aerator

An alternative to secondary ventilation in high-rise applications is the use of a stack-aerator.


A stack-aerator fitting breaks the discharge fall on each floor and as a consequence the secondary vent pipe is not required as the pressure difference stays well within the limit of 3 mbar.

The unique shape of the stack-aerator increases the capacity of the stack allowing the soil and waste flow from the higher floors to smoothly converge with the flow on the lower floor.

Stack-aerator capacity

Maximum drainage flow for the stack-aerator is illustrated below.

Stack size (mm)	Maximum capacity (l/s)
110	7.6
160	13.5



3. Active Drainage Ventilation

An active ventilated system provides relief at the Point Of Need (PON) by removing or attenuating an incoming pressure transient that, if left, could lead to trap seal depletion.

The single stack solution with the Studor P.A.P.A. and AAVs is ideal for high-rise applications, eliminating the need for roof penetrations.

The combination of the P.A.P.A., Maxi-Vent and Mini-Vent air admittance valves support a complete system to limit pressure fluctuations, guaranteeing the integrity of the traps.


Benefits of single stack with P.A.P.A system:

- Provides effective protection against positive/negative pressures in the drainage system
- Scientifically proven and tested for total peace of mind
- Reduces installed service space, slab & roof penetrations and passive fire protection measures

P.A.P.A. capacity

Maximum drainage flow for P.A.P.A. is illustrated below:

Stack size (mm)	Maximum capacity (l/s)
110	7.3
160	18.3




Typical Middle East soil & waste layout



Shown below is a typical bathroom installation using Marley Plumbing & Drainage products. The installation consists of a separate soil and waste stack, which may not be required in all applications where one stack will suffice.

This diagram shows a range of ways of connecting waste to a soil stack and the typical connections to appliances.



Joining

Soil systems are ring seal jointed. It is important that the pipe is fully pushed into the socket, except when allowing for thermal movement (see below). Waste systems are solvent weld jointed, using expansion couplings where necessary.

Sizing of soil stacks

It is recommended that the guidance given within BS EN 12056, part 3 be adopted when sizing soil stacks. Marley Plumbing & Drainage offer a range of soil and waste pipework in sizes up to 160mm which generally covers all the requirements of high rise buildings commonly constructed in the Gulf region. For further details about methods of soil stack sizing contact your local sales representative.




Pipe support

Plastic coated metal socket clips, SC41 are designed to fit ring seal sockets and act as an anchor bracket. PVCu brackets are used as an intermediate support, SC45.

The table below indicates the maximum recommended support centres:

Pipe material	BS Nominal pipe size	Horizontal support (m)	Vertical support (m)
PVCu Polypropylene	21.5	0.50	1.20
	32	0.50	1.20
	40	0.50	1.20
PVCu ABS	32	0.50	1.20
	40	0.50	1.20
	50	0.60	1.20
PVCu	82	1.00	2.00
	110	1.00	2.00
	160	1.20	2.00



Bends at the base of soil stacks

Bends at the base of vertical stacks should be of long radius and have a minimum centre line radius of 200mm on a 110mm nominal size stack. Two 45° bends may also be used as an alternative to provide the change of direction and connection to the building drain. The same design principle should also be adopted where offsets occur in stacks of one or more storey height.

Thermal movement

A 3m length of PVCu pipe will increase in length by approximately 3.6mm when subjected to a 20°C temperature variation. Therefore it is important to ensure that any movement is controlled and ring seal joints are installed to accommodate any expansion. Fig 1.

Waste systems should include an expansion coupling where pipe length exceeds 1.8m or between fixed points. Fig 2.




Fig 2

Typical floor detail showing installation method to accommodate for thermal movement at each floor level






Fig 1

Branches at the base of soil stacks

For single dwellings up to three storeys high, the distance between the centre line of the lowest branch connection and the invert of the drain should be at least 450mm. For multi-storey systems up to five storeys high, the minimum distance should be 740mm, up to twenty storeys; a separate drain connection is required to level one. Over twenty storeys, levels one and two require a separate drain connection.



Sizing of soil stacks

It is recommended that the guidance given within BS EN 12056, part 3 be adopted when sizing soil stacks. Marley Plumbing & Drainage offer a range of soil and waste pipework in sizes up to 160mm which generally covers all the requirements of high rise buildings commonly constructed in the Gulf region.

Calculation of Flowrate

Waste water flowrate Q_{ww} is the expected flowrate of waste water in a part or in the whole drainage system where only domestic sanitary appliances are connected to the system.

$Q_{ww} = K \sqrt{\sum DU}$

Where: Q_{ww} = waste water flowrate (l/s)

K = Frequency factor (table 2)

$\sum DU$ = Sum of discharge units (table 1)

Table 1

Appliance	Discharge Units (DU), l/s
WC, 6L cistern (1.2 - 1.7L/s)	1.7
Wash basin	0.3
Bath	1.3
Shower tray (no plug)	0.4
Kitchen sink	1.3
Urinal (cistern flush) per person	0.2
Bidet	0.3
Dishwasher, domestic	0.2
Washing machine, up to 6 kg	0.6
Washing machine, up to 12 kg	1.2

Table 2


Frequency of Use Factors	
Intermittent use, e.g. House, flat, offices	0.5
Frequent use, e.g. Hotel, school, hospital	0.7
Congested use, e.g. Public use	1.0
Special use, e.g. Laboratory	1.2

Vertical Soil Stack Capacity

Primary Ventilated Stack Option	DU	Secondary Ventilated Stack Option	DU
82mm Discharge Stack (no WC's)	2.6	82mm Stack & 50mm 2nd Vent (no WC's)	3.4
110mm Discharge Stack	5.2	110mm Stack & 50mm 2nd Vent	7.3
160mm Discharge Stack	12.4	160mm Stack & 82mm 2nd Vent	18.3

Floor gully

Trapped floor gullies are suitable for use as a shower outlet in bathrooms, wet rooms or as floor gullies for washdown areas in domestic, public and commercial buildings. The floor gully either has a 50mm or 82.4mm outlet, with three waste pipe inlets. The SFG42AS and SFG43AS provide a minimum 75mm water seal. The fitting is supplied with a loose base so that the body height can be reduced for casting in a shallow slab. A stainless steel grating, SGG4 or PVCu grating, SGG3 are available.



WC Connectors

Our comprehensive range is one of the largest on the market, and covers spigots of 74mm – 114mm, ensuring an accurate fit, regardless of the make and model of sanitary chinaware.

Selecting the right WC connector

Measure the OUTER diameter of your spigot.



Measure the INNER diameter of your pipe.



Then take a look at the dimensions provided for the individual connectors to find the best matches.

Know your WC pan spigot


KEY	SIZE	PIPE SUITABILITY	BRITISH STANDARD
PAGE: 24 – 28	97-108 mm	Modern & New Pans	BS 5503 & BS 5504
PAGE: 29	108-114 mm	Old & Syphonic Pans	BS 1213
PAGE: 30 – 31	76-95 mm	Stainless Steel Pans	—

Know your pipe

KEY	SIZE	PIPE SUITABILITY	BRITISH STANDARD
STANDARD ❶	99-105 mm	uPVC / Clay / Cast Iron	BS 4514/BS 4660/BS 65/BS 416
CAST IRON ❷	88-92 mm	Traditional Cast Iron	—
OLD ❸	74-77 mm	—	—
COPPER ❹	105-108 mm	Copper	—

All WC connectors are made to fit pans conforming to BS 5503 and BS 5504, including ones with bosses.

Sealing flanges



When connecting a WC connector to the pan spigot, the sealing flanges must be pushed inside with the pipe.

Don't pull the other sealing flange out over the top of the pan spigot – it may lead to leaks.



MKS1 vs MKS2

It's easy to get it right!

When you install a new toilet, in a new build development, you should use a MKS2 WC connector. When you refurbish an old toilet, you need to use a MKS1 WC connector (see page 69).

Use MKS1 on an installation, where it's been DONE!

Use MKS2 on an installation, where it's all NEW!

Make sure you know your pans and spigots

Pan dimensions

- 97 – 108mm Modern Pans
- 108 – 114mm Old Pans
- 76 – 96mm Stainless Steel

Spigot sizes

- ❶ 99 – 105mm Standard
- ❷ 88 – 92mm Cast Iron
- ❸ 74 – 77mm Old
- ❹ 105 – 108mm Copper


Multilink

Multilink is a unique fitting which sleeves the fins of all 99 – 105mm outlet Multikwik pan connectors.

Enabling direct connection to be made to the inlet of another pan connector.



Space Saver Bend



Soil Pipe Extensions

Available for 4", 3½" and 3" a Multikwik Soil Pipe Extension can be cut to required length, removing the unsightly existing pipe within the bathroom.



Traps



Multifit Nut & Seal

All Multikwik traps have a multifit nut and seal that allow connection to push fit, solvent and copper pipes. The thumb recesses make it easy to tighten, even with wet hands to ensure a 'fit and forget' installation every time!



Water Seal

BS EN 12056-2:2000 states that traps which discharge to a soil stack should have a 75mm seal. Other seal depths can be installed, if installation with required seal depth isn't possible due to size restrictions.

- 50mm water seal traps can be fitted to baths, shower trays and basins with spray taps and no plugs.
- 38mm water seal traps can be used on ground floors when connecting to flat bottomed appliances that discharge to a back inlet gully.



Resealing trap

- ❶ When syphonic action occurs, air gets drawn through the bypass device, allowing an air break.
- ❷ Once the negative pressure stops, the water goes back and reseals the trap.



Bottle Trap Resealing


The resealing function helps to prevent loss of water. Easily removed and cleaned to ensure 100% reliability.

Multi position outlet

The multi position outlet adjusts 360° for installations where space is at a premium or the pipework is misaligned.



To ensure accuracy and efficiency all Multikwik traps have unique slip ring colours to aid size identification.



Size guide

32mm


Hand basin
Bidet
Drinking fountain
Kitchen appliances

40mm

Bath
Shower
Sink
Urinal

50mm


Range of basins
Range of urinals
Catering sinks
Hospital appliances



Access components

Access is required to drainage installations for testing, inspection and removal of debris. Access to drainage, allowing rodding in both directions, can be provided by inspection chambers. Rodding eyes provide access for clearance of debris in the direction of flow only and should only be used in conjunction with an access chamber or manhole at a point downstream. Generally speaking, access should be provided at all changes in direction, gradient or pipe size, unless rods can pass through unimpeded.

A range of access components are available, including the 450mm inspection chamber (shown here) which can be used as an alternative to traditional manholes for depths up to 1.2 metres.




Gullies

Gullies, used as a method of collecting surface water to discharge to a drain. If an untrapped gully is used (sometimes necessary due to space restriction), it must be trapped using a UG42, UG42S or UG44 before entering the drainage system.

The Marley bottle gully is ideal for new or replacement installations. Accepts waste and rainwater pipes. A fully rotating gully body allows the outlet to face the required direction of the drain connection. A removable rubber plug provides access for cleaning.

A comprehensive range of gullies are available, see page 48.



Installation procedure for bottle gully

1. Cut raising piece to required length by saw cutting midway between external corrugations.
2. Remove sealing ring from gully frame spigot and place in first corrugation of raising piece.
3. Lubricate and push fit raising piece into top of gully body.
4. Gully frame spigot can then be solvent welded into top of raising piece. The gully grating may be secured to the frame if necessary with two 6 x 13mm self tapping pan head corrosion resistant screws (not supplied).

British & European Standards

BS EN 1329-1 Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure – PVCu.	BS EN 681-1 Elastomeric seals. Material requirements for pipe joint seals used in water and drainage applications. Part 1 vulcanised rubber.
BS EN 1451-1 Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure – polypropylene.	BS 4660 & BS EN 1401 Thermoplastics ancillary fittings of nominal sizes 110 and 160 for below ground gravity drainage and sewerage.
BS EN 1519-1 Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure – polyethylene.	BS 4962 Specification for plastic pipes and fittings for use as subsoil field drains.
BS 4514 Specification for PVCu soil and ventilating pipes, fittings and accessories.	BS EN 14680 Adhesives for non-pressure thermoplastic pipe systems.
BS EN 1566-1 Specification for thermoplastics waste pipe and fittings.	BS 7158 Plastic inspection chambers for drains and sewers.
BS 5255 Specification for thermoplastics waste pipe and fittings.	BS EN 124 Gully tops and manhole tops for vehicular and pedestrian areas. Design requirements, type testing, marking, quality control.
BS EN 1455-1 Plastics piping systems for soil and waste (low and high temperature) within the building structure – ABS.	BS EN 295 Vitrified clay pipes & fittings and pipe joints for drains and sewers.
BS 5627 Specification for plastics connectors for use with horizontal outlet vitreous china WC pans.	BS EN 681-1 Elastomeric seals. Material requirements for pipe joint seals used in water and drainage applications.
BS EN 14680 Specification for adhesives for non-pressure thermoplastics pipe systems.	BS EN 752 Drain & Sewer Systems outside buildings.
	BS EN 1295-1 Structural design of buried pipelines under various conditions of loading. General requirements.

BS EN 1610 Construction & Testing of Drains & Sewers.
BS EN 13476-3 Plastics piping systems for non-pressure drainage and sewerage, structured wall piping systems with smooth bore and profiled external surface.
BBA 11/H172 Quantum Highway Drainage System. 375-600mm pipes and couplings.
BBA 88/1977 Marley Underground Drainage System.
BBA 09/H146 Quantum Highway PVCu Twinwall Drainage System.
BBA 94/2985 Marley Quantum Sewer PVCu Twinwall Underground Drainage and Sewerage System.
BBA 98/3486 Marley Quantum Highway PVCu Twinwall Surface Water Drainage System.
WIS 4-08-01 Bedding and sidefill materials for buried pipelines.
BS EN ISO 9001 Quality management systems.
BS EN ISO 14001 Environmental management systems requirements with guidance for use.

Colour Key:

W: White B: Black G: Grey Y/B: Yellow & Blue NU: Neutral BL: Blue O: Orange

STANDARDS

British Standards

A wide range of components featured in this guide conform to British Standard Specifications, many items bear the British Standards Institution’s Kite Mark symbol, , as indicated throughout this price list. The presence of this mark on, or in relation to, a product is an assurance that the goods have been produced under a system of supervision, control and testing, operated during manufacture and including periodical inspection of the manufacturer’s works in accordance with the Certification Mark Scheme.

• Products indicated by this symbol comprise of components not covered by Marley Plumbing & Drainage BS EN ISO 9001 Scope of Registration. However these products have been fully inspected and tested in accordance with our own Quality Management System requirements.

Agrément Certificates

Certain components and systems illustrated in this guide have been independently assessed and are the subject of certification by the British Board of Agrément. These items are indicated by the BBA symbol, , throughout this price list.


Copies of Marley Plumbing & Drainage BBA Certificates are freely available from the Company upon request or by logging on to marleypd.co.uk.

PRODUCT INFORMATION

External Installation

Where ABS components are to be installed externally they must be painted to protect them from direct sunlight.

Accreditations



Note:

Marley Plumbing & Drainage products are manufactured to a constant high standard. The Company will not therefore accept responsibility for failure of any installation which includes components not supplied by us.



Export Division

Lenham, Maidstone
Kent ME17 2DE England
Telephone: +44 (0)1622 858888
Fax: +44 (0)1622 850778
marleypd.co.uk
export@marleypd.co.uk

Regional Office

PO Box 488100
Office 702
Indigo Tower
Jumeirah Lakes Towers
Dubai, UAE
Tel: +971 (0) 4 3629423
Fax: +971 (0) 4 4587599
gulf@alixaxis.com

Further information

For Technical advice
please call +44 (0)1622 852695
email: technical@marleypd.co.uk

an *OAliaxis* company

September 2018